



PRODUCT DATA SHEET

YOLO Colorhouse Inside – Primer

110410

- **ZERO VOC**
- **LOW ODOR**
- **EXCELLENT HIDE**
- **FAST DRYING**
- **WATER CLEAN-UP**

YOLO Colorhouse® began with the elemental – what to put into our paint and what to leave out. With 39 percent volume solids and Green Seal™ certification, YOLO Colorhouse performs like a premium conventional primer, yet it has low odor, no harmful chemicals, and no added solvents. YOLO Colorhouse Inside Primer has excellent hide and durability. Use YOLO Colorhouse Inside Primer for a complete zero VOC system.

USAGE A zero VOC, low odor primer for interior use.

AVAILABILITY 1 Gallon and Five gallon containers.

COVERAGE Please purchase the appropriate amount needed for the project. 350 sq. feet per gallon.

DRY TIME At 77°F and 50% humidity: dry time to touch is 30 min. and dry time to re-coat is 1 hour.

THINNING May be thinned up to .5 oz clean water/gallon, if necessary.

SURFACE PREPARATION Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, wax, and mildew. New wallboard should be vacuumed and free of dust. Remove peeling paint or loose material on surface*. Use YOLO Colorhouse Primer for new wallboard, new wood, cured masonry and plaster, spackled areas, when going from a dark to light color. New plaster or masonry must be allowed to cure 30-60 days before priming. If previously painted with latex, no priming is necessary. If previously painted in oil, dull surface and use YOLO Colorhouse primer – allow primer 24 hours to cure before top coating with YOLO Colorhouse Inside paint.

*Warning! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION Mix primer thoroughly before use. Keep lid on can of unused portion to prevent skinning. Apply with brush to cut-in edges and roller to roll wall surfaces. For brushing, use a high-quality brush. For rolling, use 3/8" to 3/4" nap roller cover. For airless sprayer – no thinning is recommended, 2000-2500 PSI, tip – .015"-.021". For conventional sprayer and HVLP, reduce up to 1 pint per gallon with clean water. Provide adequate ventilation during drying time.

CLEAN UP Remove excess primer from equipment before washing with water.

DISPOSAL Check www.earth911.org for recycling and disposal information in your area. Do not pour unused contents down drain. Pour into absorbent material, let dry and dispose with trash – OR take to hazardous waste collection program.

PHYSICAL PROPERTIES

Viscosity range: 98 ± 2 KU

Solids Volume: 39 ± 2

Solids Weight: 55 ± 2

Odor: Low non-offensive odor during painting, no odor once dried

Toxic Properties: Non-toxic

Weight: 11.3 lbs. per gallon

Theoretical VOC: Zero

Gloss: Flat (Primer)

LIMITATIONS Do not apply when surface or air temperatures are expected to drop below 45°F (7°C) or rise above 95°F (35°C) during application and drying. Keep from freezing. Not recommended for unpainted metal.

Disclaimer: All technical advice, recommendations, and services regarding this product are rendered by the Seller gratis. They are based on technical data which the Seller believes to be reliable and are intended for use by persons having skill and know-how, at their discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from this product use by Buyer whether as recommended herein or otherwise. Such recommendations, technical advice, or services are not to be taken as a license to operate under or suggest infringement of any patent.

www.yolocolorhouse.com

© 2007 YOLO Colorhouse® is a registered trademark of YOLO Colorhouse LLC.

3909 NE MLK Jr Blvd
Suite 201
Portland, OR 97212
503-493-8275

