



- **ZERO VOC**
- **100% ACRYLIC**
- **BETTER COLOR RETENTION**
- **EXCELLENT DURABILITY**
- **SUPERIOR ADHESION**

YOLO Colorhouse® Outside is a zero VOC, 100% acrylic, high performing exterior paint. With high volume solids and Green Seal™ certification, YOLO Colorhouse performs like a premium conventional paint, yet it has low odor and no solvents that contribute to low-level ozone and smog. In independent accelerated weather testing, YOLO Colorhouse Outside outperforms leading premium, conventional paints in color retention, durability, and resistance to chalking.

USAGE A 100% acrylic, zero VOC exterior architectural coating to be used on previously painted wood, cured and primed or previously painted masonry such as concrete or stucco, site-primed hardboard siding, or previously painted or primed metal. Not recommended for new cedar or redwood.

AVAILABILITY 1 Gallon containers.

COVERAGE Please purchase the appropriate amount needed for the project. 300-400 sq. feet per gallon depending on surface profile and application technique.

PRODUCT DATA SHEET

YOLO Colorhouse Outside – Satin Finish

151215

DRY TIME At 77°F and 50% humidity: dry time to touch is 40 min. and dry time to re-coat is 1-2 hours.

THINNING May be thinned up to .5 oz clean water/gallon, if necessary.

SURFACE PREPARATION Surfaces to be painted must be clean, thoroughly dry, and free of dirt, dust, grease, excessive chalking, and mildew. Remove peeling paint or loose material on surface*. Use YOLO Colorhouse Outside Primer for priming new wood, cured masonry and plaster, spackled areas, and when going from a dark to light color. New plaster or masonry must be allowed to cure 30-60 days before priming.

*Warning!: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION Mix thoroughly before use. Keep lid on can of unused portion to prevent skinning. Apply with a high quality brush, roller, or sprayer. For airless sprayer – no thinning is recommended, 2000-2500 PSI, tip – .015"-.021". For conventional sprayer and HVLP, reduce up to 1 pint per gallon with clean water. Provide adequate ventilation during drying time.

CLEAN UP Remove excess paint from equipment before washing with water.

DISPOSAL Check www.earth911.org for recycling and disposal information in your area. Do not pour unused contents down drain. Pour into absorbent material, let dry and dispose with trash – OR take to hazardous waste collection program.

PHYSICAL PROPERTIES

Viscosity range: 100 ± 2 KU

Solids Volume: 40 ± 2

Solids Weight: 55 ± 2

Odor: Low non-offensive odor during painting, no odor once dried

Toxic Properties: Non-toxic

Weight: 11.5 lbs. per gallon

Theoretical VOC: Zero

Gloss: 60° – 9-11 (Satin)

LIMITATIONS Do not apply when surface or air temperatures are expected to drop below 45°F (7°C) or rise above 95°F (35°C) during application and drying. Keep from freezing. Do not apply to unprimed metal.

Disclaimer: All technical advice, recommendations and services regarding this product are rendered by the Seller gratis. They are based on technical data which the Seller believes to be reliable and are intended for use by persons having skill and know-how, at their discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from this product use by Buyer whether as recommended herein or otherwise. Such recommendations, technical advice or services are not to be taken as a license to operate under or suggest infringement of any patent.

www.yolocolorhouse.com

© 2007 YOLO Colorhouse® is a registered trademark of YOLO Colorhouse LLC.

3909 NE MLK Jr Blvd
Suite 201
Portland, OR 97212
503-493-8275

